

Rothewald Bike Mover, Order no. 10059228 (10002793 and 10002812)

Parts list

- 1x bike mover Part I
- 1x bike mover Part II
- 1x ramp
- 1x sidestand support
- 1x mounting rail for sidestand support
- 1x securing plate for sidestand support
- 2x hexagon socket screws M10x12mm for connecting parts I and II of the bike mover
- 8x hexagon socket screws M10x12mm for connecting the mounting rail of the sidestand support to the assembled bike mover
- 14x washers
- 4x tie-down rings for lashing straps
- 2x hex bolts M10x25mm for sidestand support
- 4x rollers with parking brake
- 3x rollers without parking brake

Assembly instructions

Position part I and part II of the bike mover against each other with the roller brackets facing outwards, and attach both parts to the platform using two hexagon socket screws M10x12mm and washers. Position the mounting rail for the sidestand support against the assembled bike mover with the mounting groove facing outwards, and secure with eight washers and hexagon socket screws M10x12mm. Then position the sidestand support against the mounting rail. Hold the fastening plate against it from behind, and secure the parts using the two M10x30mm hex bolts, but only tighten them partially so that the sidestand support can still be moved. Now fit the tie-down rings for the lashing straps in the holes provided using the nut and one washer. Secure the four rollers with parking brake at the ends of the bike mover using a nut for each. Attach two rollers without parking brake on the sidestand support and one on the opposite side of the bike mover. To align the sidestand support for your motorbike, lock the rollers with parking brakes and insert the ramp in the groove provided at the end of the bike mover. Get a second person to push the motorbike onto the bike mover, then fold down the bike's sidestand and align the sidestand support so that the sidestand rests on it centrally. Fold the sidestand up again and get your helper to push the motorbike off the bike mover again. Tighten the two M10 hex bolts on the sidestand support. The bike mover is now fully assembled and ready to use.

Safety instructions for using the bike mover

Only use the bike mover on a solid, level and sound surface, and never on sand, soil or soft ground. The bike mover is designed for a maximum load of 250 kg. Never use it for a vehicle that is heavier than this. Always push the motorbike forwards onto the bike mover using the ramp.

Make sure that the sidestand is fully folded out and rests centrally on the sidestand support.

For safety, you should secure the motorbike with lashing straps attached to the tie-down rings before moving the bike. In addition, you should secure the sidestand to the frame of the bike with a lashing strap to prevent it from accidentally folding up. Before moving the bike, always remove the ramp and release the parking brakes.

The bike mover can be moved in any direction in order to make optimum use of the available space. Never move heavy vehicles on your own. Never stand on the bike mover while it is being manoeuvred.

Once you have positioned the bike mover where you want it, always secure it by locking the four parking brakes on the nylon rollers.

Care and maintenance of the bike mover

If you use the bike mover in a damp place, you can protect the external metal surfaces against corrosion by applying a hardwax car polish.

But never treat the platform (on which the motorbike wheels stand) or the sidestand support with polish or any other product that would make them shiny and slippery. Open, moving parts can be lubricated with silicone spray.

Since this is a universal product and not intended just for one particular vehicle, it is important to make sure that it is suitable for your type of vehicle before you use the product for the first time. Always follow the instructions in your vehicle owner's manual and the directions of the vehicle manufacturer. This is essential, as improper use of this product or its unsuitability for a vehicle could impair the safety of the vehicle and/or damage it.

Please contact our technics centre via the fax number 0049 (0)40-734 195-58 resp. by email: technikcenter@louis.de before using the article for the first time, if you have any questions on the product and/or these instructions. We will be happy to provide you with quick help. In this way, together we guarantee that the product is correctly assembled and used without any problems.