

## Windshields

Congratulations on the purchase of this motorcycle windshield. To ensure this product gives you long service, it is essential to observe the following instructions for use and safety instructions:

Before you start installing the windshield, please check that it is an accurate fit for your motorcycle, and that the necessary fittings, as described in the installation instructions, have been included.

Please handle the windshield and accessories with particular care so that you can return or exchange them if they aren't suitable or not really what you're looking for. Damaged or dirty windshields cannot be returned or exchanged. Of course, your warranty rights in respect of defects also apply to a used article.

Both during and after fitting, please make sure that installation of the windshield does not trap or impair the function of control cables, brake lines, speedometer cables etc. In particular, you should check this with the steering at full lock and the front fork compressed. Also check that the headlight can still be adjusted after the windshield has been fitted.

Make sure that the windshield is fitted correctly so that it is not under tension. Take care when tightening the bolts on the plastic. If a protective edge trim is included with the windshield, it must be installed for the type approval to remain valid.

If the windshield can be adjusted to suit the particular motorcycle, it should be positioned so that the airstream is directed away from the rider's helmet as far as possible. If this cannot be achieved adequately on your motorcycle, it should be considered whether the windshield can be fitted with a spoiler.

Before riding your motorbike with the new windshield fitted, be sure to check that the steering is able to move freely. The steering lock must not be restricted by the windshield. If it is restricted, you must not ride your motorcycle until this problem has been rectified. In case of doubt, you should consult your local motorcycle workshop.

Windshields may have an effect on how your motorcycle handles. After installing your windshield, you should test your motorcycle cautiously from lower to higher speeds to get a feel for how it now handles.

If you cover your motorcycle with a motorcycle cover, it's a good idea to drape a soft, clean towel over the windshield to prevent the cover from rubbing against it and causing scratches.

To avoid scratches, only clean the windshield with a soft, clean microfibre cloth and plenty of water, mild soapy water, or best of all, a visor cleaner. Very dirty windshields must first be rinsed off with a powerful water jet to remove any dust and sand particles. Never use cleaners containing alcohol (many household cleaners and glass cleaners, for example, contain alcohol), as they will attack the surface of the windshield and may leave marks. Obstinate dirt caused by insects can easily be removed with visor cleaner. Fine scratches and surfaces that have become matt can be treated with a special polish suitable for plastic/acrylic glass (e.g. from Dr. Wack). Never clean or polish the windscreen in full sun to avoid damaging the surface. (This also applies to cleaning and polishing the rest of your bike).

If you have any questions about the product or these instructions, please contact our Technical Centre by fax on 0049 (0)40 734 193-58 or by e-mail at: [technikcenter@louis.de](mailto:technikcenter@louis.de) before you install or use the product. We will be pleased to provide prompt assistance. This is the best way to ensure that your product is installed properly and used correctly.