

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.03.2016

V - 5

Revision: 16.03.2016

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** S100 Helmet Lining Cleaner
- **Article number:** 2160
- **1.2 Relevant identified uses of the substance or mixture and uses advised against** Void
- **Application of the substance / the mixture** Cleaning agent/ Cleaner
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Dr.O.K.Wack Chemie GmbH
Bunsenstrasse 6
D - 85053 Ingolstadt
Tel. +49 841-6350 Fax +49 841-63558
www.wackchem.com
wack.info@wackchem.com
- **Further information obtainable from:** Safety department
- **1.4 Emergency telephone number:** During business hours: +49 841 63523

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS07

Eye Irrit. 2 H319 Causes serious eye irritation.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms** GHS02, GHS07
- **Signal word** Danger
- **Hazard statements**
H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.
H319 Causes serious eye irritation.

- **Precautionary statements**
 - P101 If medical advice is needed, have product container or label at hand.
 - P102 Keep out of reach of children.
 - P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 - P251 Do not pierce or burn, even after use.
 - P260 Do not breathe spray.
 - P211 Do not spray on an open flame or other ignition source.
 - P271 Use only outdoors or in a well-ventilated area.
 - P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 - P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
 - P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.

(Contd. on page 2)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 16.03.2016

V - 5

Revision: 16.03.2016

Trade name: S100 Helmet Lining Cleaner

(Contd. of page 1)

· **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· **3.2 Mixtures**

· **Description:** Mixture of the substances with nonhazardous additions.

· **Dangerous components:**

CAS: 64-17-5 EINECS: 200-578-6 Reg.nr.: 01-2119457610-43-xxxx	ethanol ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319	5-<10%
CAS: 106-97-8 EINECS: 203-448-7	butane ⚠ Flam. Gas 1, H220; Press. Gas C, H280	3-5%
CAS: 74-98-6 EINECS: 200-827-9	propane ⚠ Flam. Gas 1, H220; Press. Gas C, H280	3-5%
CAS: 68155-09-9 EINECS: 268-938-5 Reg.nr.: 01-2119488703-29	Amides,coco,N-(3-(dimethylamino)propyl),N-oxides ⚠ Eye Dam. 1, H318; ⚠ Skin Irrit. 2, H315	1-<3%

· **SVHC** None

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· **4.1 Description of first aid measures**

· **General information:** Take affected persons out into the fresh air.

· **After inhalation:**

Supply fresh air.

Seek medical treatment in case of complaints.

· **After skin contact:** Rinse with warm water.

· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:**

If swallowed, do not induce vomiting; seek medical advice immediately and show this container or label.

· **4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

· **4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

SECTION 5: Firefighting measures

· **5.1 Extinguishing media**

· **Suitable extinguishing agents:**

Carbon dioxide

Fire-extinguishing powder

Water haze

Foam

· **For safety reasons unsuitable extinguishing agents:** Water with full jet

· **5.2 Special hazards arising from the substance or mixture**

Formation of toxic gases is possible during heating or in case of fire.

· **5.3 Advice for firefighters**

· **Protective equipment:** Wear self-contained respiratory protective device.

(Contd. on page 3)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 16.03.2016

V - 5

Revision: 16.03.2016

Trade name: S100 Helmet Lining Cleaner

(Contd. of page 2)

Additional information

Cool endangered receptacles with water spray.
Danger of bursting.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources.
Ensure adequate ventilation
Particular danger of slipping on leaked/spilled product.

6.2 Environmental precautions: No special measures required.

6.3 Methods and material for containment and cleaning up:

Pick up mechanically.
Clean the affected area carefully; suitable cleaners are:
Warm water

6.4 Reference to other sections

See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.
Do not spray onto a naked flame or any incandescent material.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles:

Store in a cool location.
Observe official regulations on storing packagings with pressurised containers.

Information about storage in one common storage facility: Store away from foodstuffs.

Further information about storage conditions:

Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.
Protect from heat and direct sunlight.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

Additional information about design of technical facilities: No further data; see item 7.

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

DNELs

64-17-5 ethanol

Oral	DNEL system. effects (long-term)	87 mg/kg KG/Tag (Consumer)
Dermal	DNEL systemic effects	343 mg/kg (Worker)

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 16.03.2016

V - 5

Revision: 16.03.2016

Trade name: S100 Helmet Lining Cleaner

(Contd. of page 3)

Inhalative	DNEL system. effects (long-term)	206 mg/kg KG/Tag (Consumer)
	DNEL system. effects (long-term)	114 mg/m ³ (Consumer)
		950 mg/m ³ (Worker)
	DNEL local effects (short-term)	950 mg/m ³ (Consumer)
		1900 mg/m ³ (Worker)

· PNECs

64-17-5 ethanol

PNEC	0,79 mg/l (Meerwasser)
	0,96 mg/l (fresh water)

· **Additional information:** The lists valid during the making were used as basis.

· 8.2 Exposure controls

· Personal protective equipment:

· General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.
Wash hands before breaks and at the end of work.
Avoid contact with the eyes.

· **Respiratory protection:** Not necessary if room is well-ventilated.

· **Protection of hands:** Not required.

· **Material of gloves:** Not required.

· **Penetration time of glove material:** Not required.

· **Eye protection:** Not required.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

Form:	Aerosol
Colour:	Light yellow
· Odour:	Fruit-like
· Odour threshold:	Not determined

· **pH-value:** Void

· Change in condition

Melting point/Melting range: Undetermined.
Boiling point/Boiling range: -44 °C

· **Flash point:** -97 °C

· **Ignition temperature:** 365 °C

· **Self-igniting:** Product is not selfigniting.

· **Danger of explosion:** Heating may cause an explosion.

· Explosion limits:

Lower:	Not determined
Upper:	Not determined

· **Density:** Not determined.

· **Solubility in / Miscibility with water:** Fully miscible.

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 16.03.2016

V - 5

Revision: 16.03.2016

Trade name: S100 Helmet Lining Cleaner

(Contd. of page 4)

- **Viscosity:**
 - Dynamic:** Not determined
 - Kinematic:** Not determined
- **9.2 Other information** No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.
- **10.3 Possibility of hazardous reactions** Reacts with strong oxidising agents.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** Store away from oxidising agents.
- **10.6 Hazardous decomposition products:**
No decomposition if used and stored according to specifications.
In case of fire, the following can be released:
Carbon monoxide and carbon dioxide

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

64-17-5 ethanol

Oral	LD50	10470 mg/kg (rat)
Dermal	LD50	> 2000 mg/kg (rabbit)
Inhalative	LC50/4 h	>20 mg/l (mouse)

106-97-8 butane

Inhalative	LC50/4 h	658 mg/l (rat)
------------	----------	----------------

- **Specific symptoms in biological assay:** Not determined
- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation**
Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

EU

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 16.03.2016

V - 5

Revision: 16.03.2016

Trade name: S100 Helmet Lining Cleaner

(Contd. of page 5)

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:

64-17-5 ethanol

EC50/48h > 10000 mg/l (daphnia magna)

LC50/48h 8140 mg/l (leuciscus idus)

68155-09-9 Amides,coco,N-(3-(dimethylamino)propyl),N-oxides

LC50/96h 18 mg/l (oncorhynchus mykiss)

EC50/48h 16 mg/l (daphnia magna)

12.2 Persistence and degradability No further relevant information available.

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

Additional ecological information:

General notes:

The surfactant(s) contained in this preparation complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

12.5 Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation Disposal must be made according to official regulations.

European waste catalogue

16 05 04* gases in pressure containers (including halons) containing hazardous substances

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

14.1 UN-Number

ADR, IMDG, IATA UN1950

14.2 UN proper shipping name

ADR 1950 AEROSOLS

IMDG AEROSOLS

IATA Aerosols, flammable

14.3 Transport hazard class(es)

ADR

Class 2 5F Gases.

Label 2.1

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 16.03.2016

V - 5

Revision: 16.03.2016

Trade name: S100 Helmet Lining Cleaner

(Contd. of page 6)

· IMDG, IATA	
· Class	2.1
· Label	2.1
· 14.4 Packing group	
· ADR, IMDG, IATA	Void
· 14.5 Environmental hazards:	None
· Marine pollutant:	No
· 14.6 Special precautions for user	Warning: Gases.
· Danger code (Kemler):	-
· EMS Number:	F-D,S-U
· Stowage Code	SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
· Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· Transport category	2
· Tunnel restriction code	D
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
No further relevant information available.
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category P3a** FLAMMABLE AEROSOLS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has been carried out.

EU

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 16.03.2016

V - 5

Revision: 16.03.2016

Trade name: S100 Helmet Lining Cleaner

(Contd. of page 7)

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

· **Abbreviations and acronyms:**

Flam. Gas 1: Flammable gases, Hazard Category 1

Aerosol 1: Flammable aerosols, Hazard Category 1

Press. Gas C: Gases under pressure: Compressed gas

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

· *** Data compared to the previous version altered.**