

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 24.07.2019

V - 8

Revision: 24.07.2019

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifier**· Trade name: **S100 Reproofing Spray**

· Article number: 3470

· 1.2 Relevant identified uses of the substance or mixture and uses advised against Void

· Application of the substance / the mixture Maintenance product

**1.3 Details of the supplier of the safety data sheet**

· Manufacturer/Supplier:

Dr.O.K.Wack Chemie GmbH

Bunsenstrasse 6

D - 85053 Ingolstadt

Tel. +49 841-6350 Fax +49 841-63558

www.wackchem.com

wack.info@wackchem.com

· Further information obtainable from: Safety department

· 1.4 Emergency telephone number: During business hours: +49 841 63523

**SECTION 2: Hazards identification****2.1 Classification of the substance or mixture**

· Classification according to Regulation (EC) No 1272/2008

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

**2.2 Label elements**

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms



GHS02 GHS07 GHS09

· Signal word Danger

· Hazard-determining components of labelling:

Naphtha (petroleum), hydrotreated light

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe spray.

P271 Use only outdoors or in a well-ventilated area.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 2)



## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 24.07.2019

V - 8

Revision: 24.07.2019

**Trade name: S100 Reproofing Spray**

(Contd. of page 1)

- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**
- **Description:** Mixture of the substances with nonhazardous additions.

- **Dangerous components:**

CAS: 64742-49-0 EC number: 921-024-6 Reg.nr.: 01-2119475514-35	Naphtha (petroleum), hydrotreated light Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336	25-50%
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-butyl acetate Flam. Liq. 3, H226; STOT SE 3, H336	15-<20%
CAS: 74-98-6 EINECS: 200-827-9	propane Flam. Gas 1, H220; Press. Gas (Comp.), H280	10-<20%
CAS: 106-97-8 EINECS: 203-448-7	butane Flam. Gas 1, H220; Press. Gas (Comp.), H280	10-<20%
CAS: 108-21-4 EINECS: 203-561-1 Reg.nr.: 01-2119537214-46	isopropyl acetate Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	5-<10%

- **SVHC** None
- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information:**  
Take affected persons out into the fresh air.  
If symptoms persist consult doctor.
- **After inhalation:**  
Supply fresh air.  
Seek medical treatment in case of complaints.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:**  
If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.
- **4.2 Most important symptoms and effects, both acute and delayed**  
No further relevant information available.
- **Hazards** If swallowed or in case of vomiting, danger of entering the lungs.
- **4.3 Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

### SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

(Contd. on page 3)



## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 24.07.2019

V - 8

Revision: 24.07.2019

**Trade name: S100 Reproofing Spray**

(Contd. of page 2)

- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**  
Formation of toxic gases is possible during heating or in case of fire.
- **5.3 Advice for firefighters**
- **Protective equipment:** Wear self-contained respiratory protective device.
- **Additional information**  
Danger of bursting.  
Cool endangered receptacles with water spray.

#### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Keep away from ignition sources.  
Ensure adequate ventilation  
Avoid contact with skin and eyes.
- **6.2 Environmental precautions:**  
Do not allow to penetrate the ground/soil.  
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

#### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**  
Use only in well ventilated areas.  
Avoid contact with skin and eyes.
- **Information about fire - and explosion protection:**  
Keep ignition sources away - Do not smoke.  
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.  
Do not spray onto a naked flame or any incandescent material.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**  
Store in a cool location.  
Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:**  
Protect from heat and direct sunlight.  
Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.
- **7.3 Specific end use(s)** No further relevant information available.

#### SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

(Contd. on page 4)



## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 24.07.2019

V - 8

Revision: 24.07.2019

**Trade name: S100 Reproofing Spray**

(Contd. of page 3)

**· 8.1 Control parameters**
**· Ingredients with limit values that require monitoring at the workplace:**

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

**· DNELs**
**64742-49-0 Naphtha (petroleum), hydrotreated light**

Oral	DNEL system. effects (long-term)	699 mg/kg (Consumer)
Dermal	DNEL system. effects (long-term)	699 mg/kg (Consumer) 773 mg/kg (Worker)
Inhalative	DNEL system. effects (long-term)	608 mg/m <sup>3</sup> (Consumer) 2,035 mg/m <sup>3</sup> (Worker)
<b>123-86-4 n-butyl acetate</b>		
Inhalative	DNEL system. effects (long-term)	35.7 mg/m <sup>3</sup> (Consumer) 300 mg/m <sup>3</sup> (Worker)

**· PNECs**
**123-86-4 n-butyl acetate**

PNEC	0.018 mg/l (Meerwasser)
	35.6 mg/l (STP)
	0.18 mg/l (fresh water)

· **Additional information:** The lists valid during the making were used as basis.

**· 8.2 Exposure controls**
**· Personal protective equipment:**
**· General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Ensure good ventilation/exhaustion at the workplace.

Avoid contact with the eyes and skin.

· **Respiratory protection:** Not necessary if room is well-ventilated.

**· Protection of hands:**

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

**· Material of gloves**

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

**· Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:** Safety glasses

EU

(Contd. on page 5)



## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 24.07.2019

V - 8

Revision: 24.07.2019

**Trade name: S100 Reproofing Spray**

(Contd. of page 4)

### SECTION 9: Physical and chemical properties

#### · 9.1 Information on basic physical and chemical properties

##### · General Information

##### · Appearance:

· Form:	Aerosol
· Colour:	Light yellow
· Odour:	Characteristic
· Odour threshold:	Not determined

· pH-value: Void

##### · Change in condition

· Melting point/freezing point:	Undetermined.
· Initial boiling point and boiling range:	-44 °C

· Flash point: -97 °C

· Flammability (solid, gas): Not applicable.

· Ignition temperature: 260 °C

· Decomposition temperature: Not determined.

· Auto-ignition temperature: Product is not selfigniting.

· Explosive properties: Heating may cause an explosion.  
In use, may form flammable/explosive vapour-air mixture.

##### · Explosion limits:

· Lower:	1.2 Vol %
· Upper:	10.9 Vol %

· Vapour pressure at 20 °C: 8300 hPa

· Density:	Not determined.
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not applicable.

· Solubility in / Miscibility with water: Not miscible or difficult to mix.

· Partition coefficient: n-octanol/water: Not determined.

##### · Viscosity:

· Dynamic:	Not determined
· Kinematic:	Not determined

· 9.2 Other information: No further relevant information available.

### SECTION 10: Stability and reactivity

· 10.1 Reactivity: No further relevant information available.

#### · 10.2 Chemical stability

##### · Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.  
Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.

· 10.3 Possibility of hazardous reactions: Reacts with strong oxidising agents.

· 10.4 Conditions to avoid: No further relevant information available.

· 10.5 Incompatible materials: Store away from oxidising agents.

(Contd. on page 6)



## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 24.07.2019

V - 8

Revision: 24.07.2019

**Trade name: S100 Reproofing Spray**

(Contd. of page 5)

- **10.6 Hazardous decomposition products:**  
 No decomposition if used and stored according to specifications.  
 In case of fire, the following can be released:  
 Carbon monoxide and carbon dioxide

#### SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

- **LD/LC50 values relevant for classification:**

##### 64742-49-0 Naphtha (petroleum), hydrotreated light

Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)
Inhalative	LC50/4 h	>20 mg/l (rat)

##### 123-86-4 n-butyl acetate

Oral	LD50	10,760 mg/kg (rat) (OECD 423)
Dermal	LD50	>14,112 mg/kg (rabbit) (OECD 402)
Inhalative	LC50/4 h	23.4 mg/l (rat) (OECD 403)

##### 106-97-8 butane

Inhalative	LC50/4 h	658 mg/l (rat)
------------	----------	----------------

##### 108-21-4 isopropyl acetate

Oral	LD50	3,000 mg/kg (rat)
------	------	-------------------

- **Specific symptoms in biological assay:** Not determined
- **Primary irritant effect:**
- **Skin corrosion/irritation**  
 Causes skin irritation.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Additional toxicological information:** Vapours may cause drowsiness and dizziness.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**  
 May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

#### SECTION 12: Ecological information

- **12.1 Toxicity**

- **Aquatic toxicity:**

##### 123-86-4 n-butyl acetate

LC50/96h	18 mg/l (Pimephales promelas) (OECD 203)
EC50/72h	647.7 mg/l (Desmodesmus subspicatus) (Wachstumshemmung)
EC50/48h	44 mg/l (daphnia magna)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.

(Contd. on page 7)





## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 24.07.2019

V - 8

Revision: 24.07.2019

**Trade name: S100 Reproofing Spray**

(Contd. of page 6)

- **Ecotoxicological effects:**
- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:**  
 Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water  
 Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.  
 Also poisonous for fish and plankton in water bodies.  
 Toxic for aquatic organisms
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

#### SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation** Disposal must be made according to official regulations.

- **European waste catalogue**

16 00 00	WASTES NOT OTHERWISE SPECIFIED IN THE LIST
16 05 00	gases in pressure containers and discarded chemicals
16 05 04*	gases in pressure containers (including halons) containing hazardous substances

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

#### SECTION 14: Transport information

- **14.1 UN-Number**
- **ADR, IMDG, IATA** UN1950
- **14.2 UN proper shipping name**
- **ADR** 1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS
- **IMDG** AEROSOLS (Naphtha (petroleum), hydrotreated light),
- **IATA** MARINE POLLUTANT AEROSOLS, flammable
- **14.3 Transport hazard class(es)**
- **ADR**
- **Class** 2.5F Gases.
- **Label** 2.1
- **IMDG, IATA**
- **Class** 2.1
- **Label** 2.1
- **14.4 Packing group**
- **ADR, IMDG, IATA** Void
- **14.5 Environmental hazards:** Product contains environmentally hazardous substances:  
Naphtha (petroleum), hydrotreated light
- **Marine pollutant:** Yes  
Symbol (fish and tree)
- **Special marking (ADR):** Symbol (fish and tree)

(Contd. on page 8)



## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 24.07.2019

V - 8

Revision: 24.07.2019

**Trade name: S100 Reproofing Spray**

(Contd. of page 7)

<ul style="list-style-type: none"> <li>· <b>14.6 Special precautions for user</b></li> <li>· <b>Danger code (Kemler):</b></li> <li>· <b>EMS Number:</b></li> <li>· <b>Stowage Code</b></li>   <li>· <b>Segregation Code</b></li> </ul>	<p>Warning: Gases.</p> <p>-</p> <p>F-D,S-U</p> <p>SW1 Protected from sources of heat.</p> <p>SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.</p> <p>SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4.</p> <p>For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2.</p> <p>For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.</p>
<ul style="list-style-type: none"> <li>· <b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code</b></li> </ul>	<p>Not applicable.</p>
<ul style="list-style-type: none"> <li>· <b>Transport/Additional information:</b></li> </ul>	
<ul style="list-style-type: none"> <li>· <b>ADR</b></li> <li>· <b>Limited quantities (LQ)</b></li> <li>· <b>Excepted quantities (EQ)</b></li>   <li>· <b>Transport category</b></li> <li>· <b>Tunnel restriction code</b></li> </ul>	<p>1L</p> <p>Code: E0</p> <p>Not permitted as Excepted Quantity</p> <p>2</p> <p>D</p>
<ul style="list-style-type: none"> <li>· <b>IMDG</b></li> <li>· <b>Limited quantities (LQ)</b></li> <li>· <b>Excepted quantities (EQ)</b></li> </ul>	<p>1L</p> <p>Code: E0</p> <p>Not permitted as Excepted Quantity</p>
<ul style="list-style-type: none"> <li>· <b>UN "Model Regulation":</b></li> </ul>	<p>UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS</p>

#### SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**  
No further relevant information available.
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category**  
P3a FLAMMABLE AEROSOLS  
E2 Hazardous to the Aquatic Environment
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has been carried out.

#### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 9)





**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 24.07.2019

V - 8

Revision: 24.07.2019

**Trade name: S100 Reproofing Spray**

(Contd. of page 8)

· **Relevant phrases**

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.

· **Classification according to Regulation (EC) No 1272/2008 Calculation method**

· **Abbreviations and acronyms:**

- Flam. Gas 1: Flammable gases – Category 1
- Aerosol 1: Aerosols – Category 1
- Press. Gas (Comp.): Gases under pressure – Compressed gas
- Flam. Liq. 2: Flammable liquids – Category 2
- Flam. Liq. 3: Flammable liquids – Category 3
- Skin Irrit. 2: Skin corrosion/irritation – Category 2
- Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
- STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
- Asp. Tox. 1: Aspiration hazard – Category 1
- Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

· **\* Data compared to the previous version altered.**